

Reply to Office Action of September 21, 2006

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A drawer type door opening/closing structure for a refrigerator, the structure comprising:

a door configured to selectively open and close a storage space formed in a refrigerator body by being drawn out and pushed into the refrigerator body in a manner in which a drawer is moved, the door being capable of being pivoted about a lower end of the door;

at least one support frame hingedly connected to a rear surface of the door thereby creating a hinge connection to allow the door to pivot about the lower end of the door and allow a storage box for storing an object to be seated behind the door;

at least one movable rail formed on the support frame and configured to be engaged with at least one guide rail formed on an inner surface of a side wall of the refrigerator body to guide movement of the at least support frame; and

at least one cover bracket protruding backward from the rear surface of the door and configured to completely cover a gap triangular space between the support frame, ~~and the~~ rear surface of the door, and the hinge connection when the door is opened.

Reply to Office Action of September 21, 2006

2. (Original) The structure as claimed in claim 1, wherein the cover bracket is located outside of the support frame when the door stands upright.

3. (Original) The structure as claimed in claim 1, wherein the door includes a door basket for storing an object, the door basket being disposed at an upper portion of the rear surface of the door.

4. (Previously Presented) The structure as claimed in claim 1, wherein the door further includes at least one tilting latch formed at one side of the rear surface of the door, the door having a lower end hingedly assembled with the support frame, the tilting latch having a latch jaw, and the support frame having a stopper pin, wherein the latch jaw and the stopper pin can be engaged with each other to limit a range within which the door can be pivoted.

5. (Currently Amended) A drawer type door opening/closing structure for a refrigerator, the structure comprising:

a door configured to selectively open and close at least one storage space in a refrigerator body by being drawn out and pushed into the refrigerator body in a manner in which a drawer is moved, the door being capable of being pivoted about a lower end of the door;

Reply to Office Action of September 21, 2006

at least one support frame hingedly connected to a rear surface of the door thereby creating a hinge connection to allow the door to pivot about the lower end of the door and allow a storage box for storing an object to be seated behind the door; and

at least one cover bracket protruding backward from the rear surface of the door and configured to completely cover a gap-triangular space formed between the support frame, ~~and the rear surface of the door,~~ and the hinge connection when the door is opened.

6. (Currently Amended) The structure as claimed in claim 5, further comprising:

at least one movable rail formed on the support frame; and

at least one guide rail formed on an inner surface of a side wall of the refrigerator body, wherein the guide rail is engaged with the movable rail, and ~~guide~~ guides movement of the support frame.

7. (Original) The structure as claimed in claim 5, wherein the cover bracket is located outside of the support frame when the door stands upright.

8. (Original) The structure as claimed in claim 5, wherein the door includes a door basket for storing an object, the door basket being disposed at an upper portion of the rear surface of the door.

Reply to Office Action of September 21, 2006

9. (Currently Amended) The structure as claimed in claim 8, wherein the door further includes at least one tilting latch formed at one side of the rear surface of the door, the ~~tilting~~ door having a lower end hingedly assembled with the support frame, the tilting latch having a latch jaw, and the support frame having a stopper pin, wherein the latch jaw and the stopper pin can be engaged with each other to limit a range within which the door can be pivoted.

10. (Previously Presented) A refrigerator comprising the structure of claim 1.

11. (Previously Presented) A refrigerator comprising the structure of claim 5.